



DC SERIES

60kW Free Standing DC Fast Charger



Features

- Simultaneously 2 DC
- Multi-standard: CCS, CHAdeMO and GB/T
- Network or standalone operation
- User authentication
- Optional cable management accessories
- Support smart charging and load balancing
- Efficiency > 94% : PF > 0.99(APFC)
- 7 inches LCD screen with user friendly interface
- OCPP 1.6 JSON
- IK10(Not including screen and RFID module), IP55
- Customization available

Applications

- Highway gas/service station
- Parking garage
- Commercial fleet operators
- EV infrastructure operators and service providers
- EV dealer workshops

Accessory



- Cable Management



DC Series

Model Name

UL, DS 60 Series

Picture



Power Specification

AC Input	Input Rating	3Φ_480Vac (+10%, -15%)
	AC Input Connection	3P+N+PE (Wye configuration), TN/TT
	Max. Input Current	DC System:3Φ100A(Typ.±1%)
	Frequency	50Hz/60Hz
	Power Factor	>0.99 @ full load
	Efficiency	≥94%
DC Output	Output Voltage Range	CCS1:150~950Vdc CHAdeMO:150~500Vdc
	Max. Output Current	CCS1:63A@950Vdc CHAdeMO/CCS1:120A@500Vdc
	Max. Output Power	DC System:60kW +
	Voltage Accuracy	±2%
	Current Accuracy	±2%

User Interface & Control

Display	7" LCD
Push Buttons	Operation buttons/ Emergency stop button
User Authentication	RFID: support ISO 14443A/B, ISO 15693, FeliCa Lite-S (RCS966) OCPP, 2D barcode, APP, Mobile payment

Communication

External	Ethernet/4G/Wi-Fi
Internal	CAN bus/RS485

Environmental

Operating Temperature	-30°C~50°C, power derating from 50°C and above
Altitude	≤ 2000m
IP Level	IP55/IK10 (not including screen and RFID module)
Cooling Method	Fan cooling

Mechanical

Cabinet Dimension(W x D x H)	700 x 331 x 1800 mm±1%
Weight	≤ 235kg±1%
Cable Length	4m

Protection

Input Protection	OVP, OCP, OPP, OTP, UVP, RCD, SPD
Output Protection	OCP, OVP, UVP, OTP, IMD

Regulation

Certificate	UL 2202, UL 2231-1/-2
Safety	NRTL - cETLus
Charging Interface	CHAdeMO V1.2, DIN 70121, GB/T 27930, (ISO15118:2020/Q4)